

COMPARISON DOCUMENT

8L CNC LATHE / 15L SLANT-PRO CNC LATHE / RAPIDTURN™ CNC CHUCKER LATHE ACCESSORY

MACHINE SPECIFICATIONS	8L	15L Slant PRO CNC LATHE
SPINDLE		
Spindle Power	1.5 hp (1.11 kW)	3 hp (2.224 kW)
Spindle Speed Ranges	Low: 180 to 2,500 RPM High: 350 to 5,000 RPM	Low: 180 to 2,500 RPM High: 250 to 3,500 RPM
Through Spindle Bore	1 in. (25.4 mm)	1.53 (39 mm) with 5C Insert Removed
Maximum Distance Between Centers	10 in. (254 mm) with Tailstock	N/A
Spindle Nose	5C	D1-4 Camlock Mount or 5C Insert
TAILSTOCK		
Taper	MT2	N/A
Diameter	0.9 in. (22 mm)	N/A
Travel	2.2 in. (55 mm)	N/A
TRAVELS AND MOTION		
X-Axis	4.5 in. (114 mm)	10 in. (254 mm)
Z-Axis	10 in. (254 mm)	12 in. (305 mm)
X- and Z-Axis Maximum Feed Rate	150 IPM (3.8 m/min)	60 IPM (1.52 m/min)
Axis Drivers (X, Z)	High-Performance Polyphase Stepper Motors w/Leadshine® Microstepping Drivers	High-Performance Polyphase Stepper Motors w/Leadshine® Microstepping Drivers
POWER		
Power Requirements (All are Single-Phase and 50/60 Hz)	115 Vac, 15A Breaker	Primary: 230 Vac, 20A Breaker Secondary: 115 Vac, 20A Breaker



MACHINE SPECIFICATIONS	8L	15L Slant PRO CNC LATHE
MACHINE SPECIFICATIONS		
Carriage Length x Width	7.25 in. x 4 in. (185 mm x 102 mm)	23.8 in. x 6.1 in. (605 mm x 155mm)
Machine Footprint	50 in. x 26 in. (1.2 m x 0.7 m)	72 in. x 42 in. (1.8 m x 1.1 m)
Typical System Weight	838 lbs. (380 kg)	1,800 lbs. (816 kg)
Maximum Swing Over Bed	8 in. (200 mm)	15 in. (381 mm)
Maximum Swing Over Carriage	4 in. (100 mm)	6.2 in. (158 mm)
Maximum System Height with Door Open	66 in. (1.6 m)	68 in. (1.7 m)
Overall System Height	52 in. (1.3 m)	68 in. (1.7 m)
ADDITIONAL OPTIONAL ACCESSORIES		
		8-Station Turret - Gang Tooling System - Automatic 5C Collet Closer

RAPIDTURN™

Turn your Tormach 770 PCNC/M/MX or 1100 PCNC/M/MX CNC mill into a 5C Chucker Lathe.

RapidTurn is easy to set up, works natively with PathPilot, and converts your CNC mill to a CNC lathe.



RapidTurn MACHINE SPECIFICATIONS

KEY DIMENSIONS

Swing-Over Base Plate	6 in. (152 mm)
Weight	60 lbs. (27.2 kg)
Footprint (W x L x H)	16.25" x 13.75" x 9.5" (415 mm x 350 mm x 240 mm)

SPINDLE

Spindle Horsepower	1 hp continuous if used with PCNC 770/1100 1.5 hp continuous if used with 770M/MX and 1100M/MX
Spindle Design	Native 5C Taper
Spindle Speed Range (Belt Driven)	Low Belt: 180 - 2,000 RPM High Belt: 300 - 3,500 RPM
Tool Holding	Spindle nose clamp with quick change tool post

TEMPERATURE

Operating Range	55° to 100°F (12° to 38°C)
-----------------	----------------------------

ELECTRICAL

Connections	Spindle motor connects to mill's VFD Spindle index sensor connects to mill's accessory port
-------------	--

All package prices subject to change without notice.

**Financing through Geneva Capital (www.gogc.com)

©2023 Tormach®. Specifications subject to change without notice.
tormach.com | Compare Tormach 8L 15L Pkgs RapidTurn [08/23]

